

UPRIGHT TANKS



PREMIUM HYDRAULIC TANK PERFORMANCE

Aluminum and steel tanks are designed for hard-working, continuous-duty applications that may generate high amounts of heat, and other applications where a metal tank is preferred. Polyethylene tanks are intended for use in intermittent-duty applications where heat buildup is not an issue.



TARGET MARKETS

- Agriculture
- Fire & Rescue
- Mining
- Mobile Equipment
- Dump & Construction
- Industrial
- Marine

KEY FEATURES

- Easy to install
- Metal tanks are designed for hard-working, continuous-duty applications
- Standard port size is 2" NPT
- Polyethylene tanks are best for intermittent-duty applications
- Suitable for a wide range of applications
- Custom sizes are available

SPECIFICATIONS

ALUMINUM TANKS				
MODEL NUMBER	VOLUME GAL. (L)	NPT PORTS *	DIMENSIONS (L x W x H)	WEIGHT LBS. (KG.) **
A035U2AAGXY	35 (132)	2	42" x 8" x 24"	66 (29.9)
A050U2AAGXY	50 (189)	2	35.25" x 13" x 26.33"	77 (34.9)
A070U2AAGXY	70 (265)	2	50.16" x 13" x 27"	90 (40.8)
A100U3AAGXY	100 (379)	3	48" x 16" x 30"	130 (59.0)
STEEL TANKS				
MODEL NUMBER	VOLUME GAL. (L)	NPT PORTS *	DIMENSIONS (L x W x H)	WEIGHT LBS. (KG.) **
S035U2AAGXY	35 (132)	2	42" x 8" x 24"	130 (59.0)
S050U2AAGXY	50 (189)	2	35.5" x 13" x 26.25"	150 (68.0)
S070U2AAGXY	70 (265)	2	50.5" x 13" x 27"	187 (84.8)
S100U3AAGXY	100 (379)	3	48" x 16.5" x 30.25"	248 (112.5)
POLYETHYLENE TANKS				
MODEL NUMBER	VOLUME GAL. (L)	NPT PORTS *	DIMENSIONS (L x W x H)	WEIGHT LBS. (KG.) **
P050U2AAGXY	50 (189)	2	36.4" x 14.5" x 27.75"	67 (30.4)
P075U2AAGXY	75 (284)	2	46.5" x 18" x 34.5"	67 (30.4)

* Standard port size is 2" NPT ** Weight includes mounting kit

NOTE: Additional porting, mounting, filter, and diffuser options listed in the model number construction. Base specifications will not change; minor weight variance may occur with the filter option.

MODEL NUMBER CONSTRUCTION

S-050-U-2-A-A-G-X-Y

Material Options

- S — Steel
- A — Aluminum
- P — Polyethylene *

Tank Capacity Options, Gal. (L)

- 035 — 35 (132.49)
- 050 — 50 (189.27)
- 070 — 70 (264.98)
- 075 — 75 (283.91) (Polyethylene Only)
- 100 — 100 (378.54)

Style Option

- U — Upright

Number of Port Options

- 2 — Two 2" Ports (35, 50, 70, & 75 Gal. Only)
- 3 — Three 2" Ports (100 Gal. Only)

*Only available in P050U2AAGXY & P075U2AAGXY

Diffuser Options

- Y — Diffuser
- N — No Diffuser (Use w/ F Code for Filter Option)

Filter Options

- X — No Filter Prep
- N — Filter Prep, Filter Not Included
- F — Filter Prep, Filter Included

Gauge Option

- G — Sight/Temp Gauge

Mounting Option

- A — Standard

Porting Options

- A — Standard
- H — High Flow (50, 70, & 100 Gal. Only)



**Muncie®
Power
Products**

A Member of the Interpump Group

IN15-32 (Rev. 08-26)

201 East Jackson Street, Muncie, Indiana 47305
800-367-7867 • Fax: 765-284-6991 • info@munciepower.com

Specifications are subject to change without notice. Visit www.munciepower.com for warranties and literature. All rights reserved. © Muncie Power Products, Inc. (2015)