

SIDE MOUNT TANKS



PREMIUM HYDRAULIC TANK PERFORMANCE

Side mount tanks are designed to fit a wide range of hydraulic applications. Steel side mount tanks work well for intermittent or continuous high-heat use and any application needing a metal tank. Polyethylene side mount tanks are intended for intermittent-duty applications where heat buildup is not an issue.



TARGET MARKETS

- Agriculture
- Fire & Rescue
- Mining
- Mobile Equipment
- Dump & Construction
- Industrial
- Marine

KEY FEATURES

- Easy to install
- Suitable for a wide range of applications
- Oil level and temperature indicator
- Return line diffusers helps prevent aeration and promotes settling of contaminants
- Steel tanks are designed for hard-working, continuous-duty applications
- Steel tank comes fully baffled
- Polyethylene tanks are best for intermittent-duty applications
- Filler breather assembly

SPECIFICATIONS

STEEL TANKS				
MODEL NUMBER	VOLUME GAL. (L)	NPT PORTS	DIMENSIONS (L x W x H)	WEIGHT LBS. (KG.)
A007B4AAGXN	7 (26.50)	4	12" x 12" x 12"	21 (9.53)
A010B4AAGXN	10 (37.85)	4	12" x 14" x 14"	25 (11.34)
A015B4AAGXN	15 (56.78)	4	14" x 16" x 16"	31 (14.06)
S007B4AAGXN	7 (26.50)	4	12" x 12" x 12"	40 (18.14)
S010B4AAGXN	10 (37.85)	4	12" x 14" x 14"	50 (22.68)
S015B4AAGXN	15 (56.78)	4	14" x 16" x 16"	62 (28.12)
S020B2ASGNN	20 (75.71)	2	14" x 17" x 20"	76 (34.47)
S025B4AAGXN	25 (94.64)	4	14.75" x 20" x 20"	84 (38.10)
S030B4AAGXN	30 (113.56)	4	14.75" x 24" x 20"	95 (43.09)
S035B2AAGNN	35 (132.49)	2	20" x 18.25" x 22"	105 (47.63)
S038B2ASGNN	38 (143.85)	2	19.17" x 22.78" x 21"	140 (63.50)
S040B4AAGXN	40 (151.42)	4	14.75" x 32" x 20"	126 (57.15)

SPECIFICATIONS

POLYETHYLENE TANKS					
MODEL NUMBER	VOLUME GAL. (L)	NPT PORTS	FILTER	DIMENSIONS (L x W x H)	WEIGHT LBS. (KG.)
P035B2AAGFN	35 (132.49)	2	—	21" x 23" x 21.75"	37 (16.78)
P035B2AAGNY	35 (132.49)	2	STANDARD	21" x 23" x 21.75"	30 (13.61)
P050B2AAGXY	50 (189.27)	2	—	31" x 23" x 22"	55 (24.95)

MODEL NUMBER CONSTRUCTION

S-040-B-4-A-A-G-X-N

Material Options

- A — Aluminum *
- S — Steel
- P — Polyethylene **

Tank Capacity Options, Gal. (L)

- 007 — 7 (26.5)
- 010 — 10 (37.9)
- 015 — 15 (56.8)
- 020 — 20 (75.7)
- 025 — 25 (96.4)
- 030 — 30 (113.6)
- 035 — 35 (132.5)
- 038 — 38 (143.8)
- 040 — 40 (151.4)
- 050 — 50 (189.3) (Polyethylene Only)

Style Option

- B — Side Mount (Box)

Number of Port Options

- 2 — One 2" Port & One 1¼" Port (Slim Line Mounting & 35 Gal. Only) OR Two 2" Ports (50 Gal. Only)
- 4 — Two 2" Ports & Two 1¼" Ports (15, 25, 30, & 40 Gal. Only) OR Two 1¼" Ports & Two 1" Ports (7 & 10 Gal. Only)

Diffuser Option

- N — No Diffuser

Filter Options

- X — No Filter Prep
- N — Filter Prep, Filter Not Included
- F — Filter Prep, Filter Included ***

Gauge Option

- G — Sight/Temp Gauge

Mounting Options

- A — Standard
- S — Slim Line **** (Use Code N or F for Filter)

Porting Option

- A — Standard

* Only available in 7, 10, & 15 Gal.

** Only available in P035B2AAGFN, P035B2AAGNY, & P050B2AAGXY

*** Only available in 15, 20, 25, 30, 35, 38, & 40 Gal.

**** Only available with Steel 15, 20, 25, 30, & 38 Gal. (20 & 38 Gal. are the only slim line gallon sizes)



**Muncie®
Power
Products**

A Member of the Interpump Group

MP15-33 (Rev. 08-26)

201 East Jackson Street, Muncie, Indiana 47305
800-367-7867 • Fax: 765-284-6991 • info@munciepower.com

Specifications are subject to change without notice. Visit www.munciepower.com for warranties and literature. All rights reserved. © Muncie Power Products, Inc. (2012)