





17 SERIES

DIRECTIONAL CONTROL VALVE



17 GPM (65 LPM) • 3,500 PSI (242 Bar) • Sectional Type • Solenoid Operated

Muncie’s 17 Series solenoid operated control valves provide flexibility you have never had before. Mount the valve assembly anywhere available on the chassis and locate your controls elsewhere in a convenient location. The sectional parallel design allows numerous combinations to be stacked together. Various work port and spool options are available to meet all your application needs.



APPLICATIONS

**Snow & Ice Control Systems • Utility Equipment • Dump Bodies
Tow Recovery Vehicles • Lube Trucks And Cranes • Small Refuse Equipment**

VALVE FEATURES

- Stackable design allows for customizing the assembly to your specific needs.
- Compact size and lightweight design.
- Precision machined spools are hard chrome plated for maximum life and corrosion resistance.
- Diamond lapped bores.
- 100% preassembled and pretested before shipping.
- Parallel circuit design permits all spools to be operated independently or simultaneously with the lightest load receiving priority.

TECHNICAL DATA

Construction	Sectional
Circuit	Parallel / Closed Center with Inlet Unloader
Capacity	12 GPM (45 LPM) Nominal 18 GPM (68 LPM) Maximum
Maximum System Pressure	3,500 PSI (242 Bar)
Maximum Tank Pressure	150 PSI (10 Bar)
Filtration	10 Micron
Spool Force	Pilot Operated 300 PSI (20 Bar) Minimum
Temperature	-20°F to 200°F (-29°C to 93°C)
Seal Type	Buna-N
Relief Valve	Pilot Operated Adjustable from 1,000 to 3,500 PSI (69 to 242 Bar) [preset at 2,000 PSI (138 Bar)]
Coil Information	Continuous Duty Rating 1.25 Amps for Each Energized Coil (9.8 Ohms Resistance @ 20°C, 12VDC), 8.50" Weatherpak Leads

PERFORMANCE AND SPECIFICATIONS

OPEN CENTER PRESSURE DROP (INLET TO OUTLET)

PRESSURE DROP
TESTS WERE RUN
AT 100 SSU (20.6 CS)
AND AT 125°F (52°C)

VALUES IN PSI (BAR)

FLOW IN GPM (LPM)	NUMBER OF SECTIONS					
	1	2	3	4	5	6
5 (19)	6 (0.41)	8 (0.54)	10 (0.68)	12 (0.82)	18 (1.23)	25 (1.70)
10 (38)	20 (1.36)	27 (1.84)	40 (2.72)	62 (4.22)	75 (5.10)	82 (5.58)
15 (57)	42 (2.86)	60 (4.08)	95 (6.46)	125 (8.51)	160 (10.89)	175 (11.91)
20 (76)	70 (4.76)	120 (8.16)	163 (11.09)	212 (14.42)	250 (17.01)	300 (20.41)

INTERNAL PRESSURE DROP (INLET TO WORK PORT)

PRESSURE DROP
TESTS WERE RUN
AT 100 SSU (20.6 CS)
AND AT 125°F (52°C)

VALUES IN PSI (BAR)

FLOW IN GPM (LPM)	NUMBER OF SECTIONS					
	1	2	3	4	5	6
3 (11)	7 (0.48)	10 (0.68)	12 (0.82)	12 (0.82)	15 (1.02)	16 (1.09)
6 (23)	15 (1.02)	20 (1.36)	23 (1.57)	25 (1.70)	28 (1.91)	30 (2.04)
9 (34)	25 (1.70)	32 (2.18)	35 (2.38)	37 (2.52)	40 (2.72)	42 (2.86)
12 (45)	40 (2.72)	45 (3.06)	50 (3.40)	53 (3.61)	55 (3.74)	57 (3.88)

INTERNAL PRESSURE DROP (WORK PORT TO OUTLET)


PRESSURE DROP
TESTS WERE RUN
AT 100 SSU (20.6 CS)
AND AT 125°F (52°C)

VALUES IN PSI (BAR)


FLOW IN GPM (LPM)	NUMBER OF SECTIONS					
	1	2	3	4	5	6
3 (11)	0.5 (0.03)	1 (0.07)	3 (0.20)	4 (0.27)	4.5 (0.31)	6 (0.41)
6 (23)	8 (0.54)	10 (0.68)	12 (0.82)	13 (0.89)	15 (1.02)	17 (1.16)
9 (34)	20 (1.36)	22 (1.50)	25 (1.70)	28 (1.91)	30 (2.04)	33 (2.25)
12 (45)	35 (2.38)	42 (2.86)	45 (3.06)	50 (3.40)	55 (3.74)	57 (3.88)

NOTE: ALL CURVES ARE FOR SHORT SECTIONS. ADD APPROX. 50 PSI (3.5 BAR) FOR TALL SECTIONS FOR USE WITH WORK PORT RELIEFS.

TYPICAL CIRCUIT



MAIN RELIEF VALVE




PORT OPTIONS

- Port Relief (Screw Adjustable)
- Pilot Operated Check Valve (Lock Valve)
- Conversion Kit for Spool Manual Override/Stroke Control Limiter (Kit #17V-36M)

OTHER SYSTEM OPTIONS


- High Pressure Filter Assembly: PLFR-451-10C50S55
- Electrical Kit (for Central Hydraulic Systems) See pg.7
- Cross Over Relief Valves: CRV-30
- Plow Float Solenoid Valve: 49T37547 (For SA Plow)
- Plow Float Solenoid Valve: 49T37546 (For DA Plow)
- Port Restrictor (Restrict In)-8: 17V-83AFF (1-6) 1 Through 6 GPM

VALVE CONSTRUCTION




DIMENSIONAL DATA

IN INCHES (MM)




Note: Energized coil directs oil to opposite side workport.
All work sections (except inlet) use a normally closed solenoid.



PORT SIZES	INLET/ OUTLET	WORK (MIDDLE)	WORK (END)
SAE O.D.T. [Standard]	-10 (7/8-14)	-8 (3/4-16)	-8 (3/4-16)
APPROX. WEIGHTS	6 lbs. (2.7 kgs.)	4.5 lbs. (2.0 kgs.)	4.5 lbs. (2.0 kgs.)


MODEL NUMBER CONSTRUCTION

INLET SECTION



WORK SECTION

See Below*



Note: For DA Dump Body Cylinder, the Down Side Relief Valve should be in the A Port.

* This section of part number used only when accessory valves or port options required. If any option is required in this part number section, a code in each field must be used.

** Recommended to be used with C Spool.

17 SERIES VALVE ASSEMBLY WORK SHEET

CUSTOMER:

VALVE SECTIONS:

MISCELLANEOUS:

INLET 17UWS01A

1st 17CS3

2nd 17CS3

3rd 17CS3

4th 17CS3

5th 17CS3

END 17CES3


STUD KIT 17V-STD-*(1-6)

ORIGINATOR:


ORDER NO:

DATE:

Layout is a guideline only for semi-standard assembly. Choices shown are popular for the described function.




ELECTRICAL KIT FOR CENTRAL HYDRAULICS SYSTEMS



KIT INCLUDES:

Mounting Bracket, Mounting Nuts & Bolts, Lexan Faceplate, Lamp & Lamp Holder, Appropriate Rocker Switches, Preassembled Wiring Harness with WeatherPak Connectors, Miscellaneous Wires and Diagrams.

ELECTRICAL KIT MODEL NUMBER CONSTRUCTION



Note: The switch panel should be mounted in the cab or in a sealed box if exposed to harsh environments.

VALVE WARRANTY

The Muncie 17 Series Valve is warranted against any defect in material and workmanship which existed at the time of sale by Muncie, according to the following provisions, subject to the requirements that the Valve must be used only in accordance with catalogue and package instructions.

The Valve is warranted for a period of one year from date of installation. If during the warranty period the Valve fails to operate to Muncie's specifications due to a defect in any part in material or workmanship that existed at the time of sale by Muncie, the defective part will be repaired or replaced, at Muncie's election, at no charge, if the defective part is returned to Muncie with transportation prepaid.

Warning. The above warranty shall terminate if any alterations or repairs are made to the Valve other than at a Service Center owned by Muncie, or if the Valve is used upon any equipment other than the equipment upon which it is first installed.

THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER OBLIGATIONS AND LIABILITIES, INCLUDING NEGLIGENCE AND ALL WARRANTIES OF MERCHANTABILITY AND SUITABILITY, EXPRESSED OR IMPLIED AND STATE MUNCIE'S ENTIRE AND EXCLUSIVE LIABILITY AND BUYER'S EXCLUSIVE REMEDY FOR ANY CLAIM OF DAMAGES IN CONNECTION WITH THE SALE, REPAIR OR REPLACEMENT OF THE ABOVE GOODS, THEIR DESIGN, INSTALLATION OR OPERATION. MUNCIE WILL IN NO EVENT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES WHATSOEVER, AND OUR LIABILITY UNDER NO CIRCUMSTANCES WILL EXCEED THE CONTRACT PRICE FOR THE GOODS FOR WHICH LIABILITY IS CLAIMED.

OTHER PRODUCTS

CALL TODAY FOR ADDITIONAL INFORMATION FOR ALL YOUR MOBILE POWER EQUIPMENT NEEDS



Electric Solenoid Valve

This compact hydraulic tank and valve package is designed especially for small underbody hoist and dump bodies, featuring a fully adjustable main relief valve and work port relief valves for double acting hoists.

Brochure MP96-06

Steel Side Mount Hydraulic Oil Reservoirs

Features a filler/breather assembly with a nylon strainer and 40 micron ¼ turn cap, a fluid level sight gauge with thermometer, internal baffle between outlet and return ports.

Brochure MP98-08

FA Series Ford Automatic PTO

By introducing a transmission driven PTO system for the optional Super Duty F-Series automatic transmission, the long requested need of an alternative to the fanbelt driven clutch pump for the automatic transmission has now been met.

Brochure MP98-01



**Muncie®
Power
Products**

Member of the Interpump Group
MP98-05 (Rev. 05-17)

201 East Jackson Street • Muncie, Indiana 47305
800-367-7867 • Fax 765-284-6991 • info@munciepower.com • www.munciepower.com
Specifications are subject to change without notice. Visit www.munciepower.com
for warranties and literature. All rights reserved. © Muncie Power Products, Inc. (2014)