

RAISING THE BAR

OUR MARATHON HOSE HOLDS STRONG



*Industry leading
pressure ratings*



**Muncie[®]
Power
Products**

INDUSTRY LEADING PRESSURE RATINGS





available in 1/4" with a 6,525 PSI WP through 1" with pressure ratings of 3,625 PSI

NO-SKIVE HOSE

IMPULSE TESTED
(up to 1,000,000 cycles)

**UTILIZES INTERPUMP
ONE PIECE G - FITTINGS**

**4:1 SAFETY
RATED**

Part Number							
	ID	Size	OD	Max WP		Min BR	Weight (approx.)
	in.		in.	bar	PSI	in.	lb/ft
BHEMM2K-04	1/4	04	0.52	450	6525	1.969	0.192
BHEMM2K-05	5/16	05	0.58	420	6090	2.362	0.222
BHEMM2K-06	3/8	06	0.67	385	5583	2.756	0.284
BHEMM2K-08	1/2	08	0.82	350	5075	3.150	0.349
BHEMM2K-10	5/8	10	0.93	350	5075	3.543	0.447
BHEMM2K-12	3/4	12	1.09	280	4060	4.725	0.531
BHEMM2K-16	1	16	1.42	250	3625	5.512	0.934

Hose construction:

Internal hose: Synthetic rubber, singular extrusion, uniform thickness

Reinforcement: 2 high tensile steel wire braids

External covering: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions

Recommended fluid:

Petroleum based hydraulic fluids, glycol-water based fluids and lubricants

Operating temperature range:

-40°F to +248°F (-40°C to +120°C) intermittent +275°F (+135°C)

INTERPUMP Marathon EXCEEDS ISO 11237 - EN857 2SC DN 19 I.D. 3/4" W. P. 280 BAR/4000 PSI

Built to INTERconnect.



MEMBERS OF THE INTERPUMP GROUP

201 EAST JACKSON STREET • MUNCIE, INDIANA 47305 • 844-745-6335 • MUNCIEPOWER.COM/HOSE