


<b>ALLISON TRANSMISSION</b>		
	<b>3000*** SERIES MUNCIE PTO SHAFT EXTENSIONS</b>	<b>ALLISON 10-BOLT OPENING</b>
	*** (EVS, RDS, SPS) (MHS, BUS, TRV OPTIONAL) MD-3050P, MD-3550P, MD-3060P, MD-3066P, MD-3560P, MD-3566P, MD-3070PT <b>Footnote (2, 4)</b>	<b>PTO DRIVE GEAR DATA:</b> 68T 10.16P L.H. <b>LOCATION:</b> Front <b>PLMF:</b> 1.775 <b>PLV:</b> 1856 FPM <b>RPM:</b> 1,000


**CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.**

PTO SERIES	<b>ALLISON 3000*** WITHOUT RETARDER OR COOLER</b>	
	LEFT SIDE	RIGHT SIDE
A20	XSMC-A30XX-X3**XX A20-A10**-**3CBPW	XSMC-A30XX-X1**XX A20-A10**-**1CBPW
CD10	49TA***** (TURN PAGE)	49TA***** (TURN PAGE)
CS10	49TA***** (TURN PAGE)	NOT AVAILABLE
CS41	NOT AVAILABLE	NOT AVAILABLE
	<b>ALLISON 3000*** WITH RETARDER</b>	
	LEFT SIDE	RIGHT SIDE
A20	XSMC-A30XX-X3**RX A20-A10**-**3CBPW	XSMC-A30XX-X1**RX A20-A1**-**1CBPW
CD10	XD10-A30XX-X3**RX CD10-A10**-**M3VX	NOT AVAILABLE
CS10	XS10-A30XX-X3**RX CS10-A10**-H3VX	NOT AVAILABLE
CS41	XS41-A30XX-X3**RX CS41-A10**-M3VX	NOT AVAILABLE
	<b>ALLISON 3000*** WITH INTEGRAL COOLER</b>	
	LEFT SIDE	RIGHT SIDE
A20	XSMC-A30XX-X4**CX A20-A10**-**5CBPW	XSMC-A30XX-X2**CX A20-A10**-**5CBPW
CD10	XD10-A30XX-X4**CX CD10-A10**-**M1VX	XD10-A30XX-X2**CX CD10-A10**-**M3VX
CS10	NOT AVAILABLE	NOT AVAILABLE
CS41	NOT AVAILABLE	NOT AVAILABLE

**IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION**

<p><b>FOOTNOTES:</b></p> <ol style="list-style-type: none"> <li>1 49TA***** part numbers are choices for aluminum housing versions of shaft extension. These are shown on back of this page.</li> <li>2 PTOs and shaft extensions for integral cooler applications must be mounted shaft high in order to clear cooler.</li> <li>3 PTO and shaft extension sold separately.</li> <li>4 No shaft extension option for Allison 3700 series transmissions.</li> <li>5 Table shows shaft extension part number on top, with corresponding PTO listed below where applicable. Some combinations are not available, and are listed as such.</li> <li>6 See Page ALLI-05 for PTO application details</li> </ol>
--

CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

<b>ALLISON TRANSMISSION</b>		
	<b>3000*** SERIES MUNCIE PTO SHAFT EXTENSIONS</b>	<b>ALLISON 10-BOLT OPENING</b>
	*** (EVS, RDS, SPS) (MHS, BUS, TRV OPTIONAL) MD-3050P, MD-3550P, MD-3060P, MD-3066P, MD-3560P, MD-3566P, MD-3070PT <b>Footnote (2, 4)</b>	<b>PTO DRIVE GEAR DATA:</b> 68T 10.16P L.H. <b>LOCATION:</b> Front <b>PLMF:</b> 1.775 <b>PLV:</b> 1856 FPM <b>RPM:</b> 1,000

PTO SERIES	OUTPUT	<b>ALLISON 3000*** WITHOUT RETARDER OR COOLER</b>	
		LEFT SIDE	RIGHT SIDE
CD10	SAE B	49TA5433A CD10-A10**-M3VX	49TA5438A CD10-A10**-M1VX
	SAE BB	49TA5432A CD10-A10**-M3VX	49TA5439A CD10-A10**-M1VX
	DIN-5462	49TA5434A CD10-A10**-M3VX	49TA5440A CD10-A10**-M1VX
	SAE B-C	49TA5435A CD10-A10**-M3VX	49TA5441A CD10-A10**-M1VX
	SAE C	49TA5436A CD10-A10**-M3VX	49TA5442A CD10-A10**-M1VX
CS10	SAE BB	49TA5448A CS10-A10**-H3VX	NOT AVAILABLE
	SAE C	49TA5449A CS10-A10**-H3VX	NOT AVAILABLE

**IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION**

**FOOTNOTES:**

- 1 PTO and shaft extension sold separately.
- 2 No shaft extension option for Allison 3700 series transmission.
- 3 Table shows shaft extension part number on top, with corresponding PTO listed below. Some combinations are not available, and are listed as such.  
For transmissions with retarder or integral cooler, see front of this page.
- 5 See Page ALLI-05 for PTO application details.