



CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

	ALLISON TRANSMISSION	RIGHT SIDE ONLY (LEFT SIDE TURN PAGE)	
FracTran		SAE 8-BOLT OPENING	
		PTO DRIVE GEAR DATA: 62T 6P 25° Spur LOCATION: Rear PLMF: .810 PLV: 3085 FPM RPM: 1,177	

6-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM of PTO	
				HI	LO	REV					TORQUE	HP
SINGLE GEAR												
SINGLE SPEED MULTI GEAR												
SH SERIES												
CLUTCH SHIFT												
1 FWD. 1 REV.												
ADAPTER TO CHANGE ROTATION			No Adapter Available					REFER TO ADAPTER GEAR ASSEMBLIES IN INDEX				



8-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM of PTO	
				HI	LO	REV					TORQUE	HP
SINGLE SPEED MULTI GEAR	828S-U6205-M4CP		Cmk	102					Included	None	500	95
	828S-U6208-M4CP		Cmk	161					Included	None	450	85
1 FWD. 1 REV.												

IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION

FOOTNOTES:

- 1 Engine Driven Drive gear requires that the Engine be turned off before engaging or disengaging PTO. Constant mesh shift option "M" is shown for this application.
- 2 Transmission pressure lube port may require straight thread fitting.

CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

ALLISON TRANSMISSION								TOP SIDE ONLY (LEFT SIDE TURN PAGE)				
		FracTran						SAE 8-BOLT OPENING				
								PTO DRIVE GEAR DATA: 48T 6P 25° Spur				LOCATION: Rear PLV: 3085 FPM
6-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM of PTO	
				HI	LO	REV					TORQUE	HP
SINGLE GEAR												
SINGLE SPEED MULTI GEAR												
SH SERIES												
CLUTCH SHIFT												
1 FWD. 1 REV.												
ADAPTER TO CHANGE ROTATION		No Adapter Available						REFER TO ADAPTER GEAR ASSEMBLIES IN INDEX				

8-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM of PTO	
				HI	LO	REV					TORQUE	HP
SINGLE SPEED MULTI GEAR	828S-U6205-M2CP		Crnk	102					Included	None	500	95
	828S-U6208-M2CP		Crnk	161					Included	None	450	85
1 FWD. 1 REV.												

IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION

FOOTNOTES:

- 1 Engine Driven Drive gear requires that the Engine be turned off before engaging or disengaging PTO. Constant mesh shift option "M" is shown for this application.
- 2 Transmission pressure lube port may require straight thread fitting..