


ALLISON TRANSMISSION		
	4000*** SERIES MUNCIE PTO SHAFT EXTENSIONS	ALLISON 10-BOLT OPENING
	*** (EVS, RDS, SPS, OFS) (MHS, BUS, TRV OPTIONAL) HD-4060P, HD-4560P, HD-4070P Footnotes (2 & 4)	PTO DRIVE GEAR DATA: 97T 10.16P L.H. LOCATION: Front PLMF: 1.775 PLV: 2648 FPM RPM: 1,000

CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.


PTO SERIES	ALLISON 4000*** WITHOUT RETARDER OR COOLER	
	LEFT SIDE	TOP SIDE
A20 and A30	XSMC-A40XX-X3**XX A*0-A10**-**3CBPW	XSMC-A40XX-X5**XX A*0-A10**-**5CBPW
CS10	XS10-A40XX-X3**XX CS10-A10**-**H3VX	NOT AVAILABLE
CS41	49TA**** (TURN PAGE)	NOT AVAILABLE
	ALLISON 4000*** WITH RETARDER	
	LEFT SIDE	TOP SIDE
A20 and A30	XSMC-A40XX-X4**RX A*0-A10**-**5CBPW	NOT AVAILABLE
CS10	XS10-A40XX-X3**RX CS10-A10**-H3VX	NOT AVAILABLE
CS41	XS41-A40XX-X3**RX CS41-A10**-M3VX	NOT AVAILABLE
	ALLISON 4000*** WITH INTEGRAL COOLER	
	LEFT SIDE	TOP SIDE
A20 and A30	XSMC-A40XX-X4**CX A*0-A10**-**5CBPW	XSMC-A40XX-X5**XX A*0-A10**-**5CBPW
CS10	NOT AVAILABLE	NOT AVAILABLE
CS41	XS41-A40XX-X4**CX CS41-A10**-H1VX	NOT AVAILABLE

IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION

FOOTNOTES:

- 1 49TA**** part numbers are choices for aluminum housing versions of shaft extension. These are shown on back of this page.
- 2 PTOs and shaft extensions for integral cooler applications must be mounted shaft high in order to clear cooler.
- 3 PTO and shaft extension sold separately.
- 4 Shaft extension choices for Allison 4700 Series transmission not shown. Only available options are XSMC-A47XX-X3**XX/ A*0-A10****3CBPW or for left side, or XSMC-A47XX-X5**XX/A*0-A10**-*5CBPW for top opening without retarder or cooler. SAE outputs only. DIN option not available.
- 5 Table shows shaft extension part number on top, with corresponding PTO listed below where applicable. Some combinations are not available, and are listed as such.
- 6 See page ALLI-06 for PTO application details.

CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

ALLISON TRANSMISSION			
	4000*** SERIES MUNCIE PTO SHAFT EXTENSIONS *** (EVS, RDS, SPS, OFS) (MHS, BUS, TRV OPTIONAL) HD-4060P, HD-4560P, HD-4070P Footnotes (2 & 4)	ALLISON 10-BOLT OPENING	
		PTO DRIVE GEAR DATA: 97T 10.16P L.H. LOCATION: Front PLMF: 1.775 PLV: 2648 FPM RPM: 1,000	
PTO SERIES	OUTPUT	ALLISON 4000*** WITHOUT RETARDER OR COOLER	
		LEFT SIDE	TOP SIDE
CS41	DIN-5462	49TA5445A CS41-A10**-H3VX	NOT AVAILABLE
	SAE B-C	49TA5446A CS41-A10**-H3VX	NOT AVAILABLE
	SAE C	49TA5447A CS41-A10**-H3VX	NOT AVAILABLE

IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION

FOOTNOTES:

- 1 PTO and shaft extension sold separately.
- 2 Shaft extension choices for Allison 4700 Series transmission not shown. Only available options are XSMC-A47XX-X3**XX/ A*0-A10***3CBPW for left side or XSMC-A47XX-X5**XX/ A*0-A10**-**5CBPW for top opening without retarder or cooler. SAE outputs only. DIN option not available.
- 3 Table shows shaft extension part number on top, with corresponding PTO listed below where applicable. Some combinations are not available, and are listed as such.
- 4 For transmissions with retarder or integral cooler, see front of this page.
- 5 See Page ALLI-06 for PTO application details.