CATERPILLAR TRANSMISSION

LOWER-RIGHT SIDE ONLY






TH48FT-E80

(THIS OPENING IS LOWER ON THIS SIDE)

PTO DRIVE GEAR DATA:


51T 6P 20° PA Spur LOCATION: Front

PLMF: .808 **PLV:** 2715 FPM **RPM:** 1,220



	6-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	HI LO REV		ADAPTER	SPACER	STUD KIT	SHIFT TYPE	@ 1,000 RP		
RPM.	SINGLE GEAR	MODEL NOMBER	NOTES	HOTATION		LO	ILLV					TONQUE	nr
UTPUT SHAFT SPEED NOT TO EXCEED 2,500	SINGLE SPEED MULTI GEAR	TG8S-U6804-M1BP TG8S-U6805-M1BP TG8S-U6806-M1BP TG8S-U6807-M1BP TG8S-U6808-M1BP TG8S-U6809-M1BP	1, 2 1, 2 1, 2 1, 2 1, 2 1, 2 1, 2	Crnk Crnk Crnk Crnk Crnk Crnk	93 122 158 186 228 239					Included Included Included Included Included Included	Wire Wire Wire Wire Wire	285 270 245 230 230 205	54 51 47 44 44 39
	SH SERIES												
	CLUTCH SHIFT	CS8S-U6003-H1BP CS8S-U6004-H1BP CS8S-U6005-H1BP CS8S-U6807-H1BP CS8S-U6809-H1BP	3 3 3 3 3	Crnk Crnk Crnk Crnk Crnk	85 114 122 182 226					Included Included Included Included Included	Power Power Power Power	300 300 300 300 300 275	57 57 57 57 57 52
0	1 FWD. 1 REV.												
Σ.	ADAPTE	R TO CHANGE ROTATION		No Ada	ailable		REFER TO ADAPTER GEAR ASSEMBLIES IN INDEX						

8-BOLT	PTO	FOOT	SHAFT	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT	INTERMITTENT RATING @ 1,000 RPM of PTO	
TYPE	MODEL NUMBER	DEL NUMBER NOTES ROTATION		HI	LO	REV	ADAI IEI	OI AOLII	OTOD IXII	TYPE	TORQUE	HP
SINGLE SPEED MULTI GEAR	828S-U6805-M1CP 828S-U6808-M1CP 828S-U6810-M1CP 828S-U6813-M1CP 828S-U6819-M1CP	2 2 2 2 2	Crnk Crnk Crnk Crnk Crnk	86 137 183 243 326					Included Included Included Included Included	Lever Lever Lever Lever	500 450 410 375 300	95 85 78 71 57
1 FWD. 1 REV.												



FOOTNOTES:

- TG Series input gear 03T34284
- 2 Transmission drive gear is engine driven and constant mesh PTOs are recommended.
- 3 Hydraulic activation HOSE KIT 131-2-0001 recommended, sold separately.