




CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

CHELSEA TRANSMISSION								RIGHT SIDE ONLY (LEFT SIDE TURN PAGE)				
 <div style="text-align: center;"> <b>912AH SPLIT SHAFT</b> Footnote (1)                 </div>								SAE 8-BOLT OPENING				
								PTO DRIVE GEAR DATA:				
								39T 6P 20° Spur	PLMF: .810			
								LOCATION: Front	RPM: 1,000			
								PLV: 1702 FPM				
6-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM of PTO	
				HI	LO	REV					TORQUE	HP
SINGLE GEAR												
SINGLE SPEED MULTI GEAR	TG8S-U6804-C1BX	2, 4	Crnk	59					Included	Cable	285	54
	TG8S-U6805-C1BX	2, 4	Crnk	76					Included	Cable	270	51
	TG8S-U6806-C1BX	2, 4	Crnk	99					Included	Cable	245	47
	TG8S-U6807-C1BX	2, 4	Crnk	117					Included	Cable	230	44
	TG8S-U6808-C1BX	2, 4	Crnk	144					Included	Cable	230	44
	TG8S-U6809-C1BX	2, 4	Crnk	150					Included	Cable	205	39
	TG8S-U6812-C1BX	2, 4	Crnk	184					Included	Cable	210	40
	TG8S-U6813-C1BH	2, 4	Crnk	210					Included	Cable	210	40
	TG8S-U6815-C1BH	2, 4	Crnk	236					Included	Cable	195	37
TG8S-U6818-C1BH	2, 4	Crnk	280					Included	Cable	175	33	
SH SERIES	SH8S-U6005-E1BX		Crnk	77					Included	Elec/Air	400	76
	SH8S-U6807-E1BX	4	Crnk	113					Included	Elec/Air	400	76
	SH8S-U6809-E1BX	4	Crnk	140					Included	Elec/Air	375	71
CLUTCH SHIFT	CS8S-U6003-E1BX		Crnk	54					Included	Power	300	57
	CS8S-U6004-E1BX		Crnk	70					Included	Power	300	57
	CS8S-U6005-E1BX		Crnk	77					Included	Power	300	57
	CS8S-U6806-E1BX		Crnk	90					Included	Power	300	57
	CS8S-U6807-E1BX	4	Crnk	113					Included	Power	300	57
	CS8S-U6809-E1BX	4	Crnk	140					Included	Power	275	52
1 FWD. 1 REV.	RL8S-U6803-L3BX	3	Crnk	43		43			Included	Lever	200	38
	RL8S-U6805-L3BX		Crnk	89		89			Included	Lever	200	38
ADAPTER TO CHANGE ROTATION		40TU6886-1 Change PTO arrangement to "2", multiply speed by 1.4					REFER TO ADAPTER GEAR ASSEMBLIES IN INDEX					



8-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM of PTO	
				HI	LO	REV					TORQUE	HP
SINGLE SPEED MULTI GEAR	828S-U6805-L1CX		Crnk	54					Included	Lever	500	95
	828S-U6808-L1CX		Crnk	86					Included	Lever	450	85
	828S-U6809-L1CX		Crnk	106					Included	Lever	410	78
	828S-U6810-L1CX		Crnk	115					Included	Lever	410	78
	828S-U6812-L1CX		Crnk	132					Included	Lever	375	71
	828S-U6813-L1CX		Crnk	153					Included	Lever	375	71
	828S-U6815-L1CX		Crnk	167				(2) 23M80062	Included	Lever	350	67
	828S-U6819-L1CX		Crnk	205				23M80248	20MK8817	Lever	300	57
1 FWD. 1 REV.												




**IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION**

- FOOTNOTES:**
- 1 Speeds shown with main transmission in direct drive.
  - 2 TG Series Input Gear: #03T34284 — Refer to kit program on pages 10 & 11.
  - 3 RL Series with combined reduction gear box.
  - 4 Optional: U68 Input Gear can be replaced by S68 Input Gear to obtain output speed 92% of speed shown. Add spacer 23M80190 and stud kit 20MK8808.

CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

CHELSEA TRANSMISSION								LEFT SIDE ONLY (RIGHT SIDE TURN PAGE)				
		<b>912AH SPLIT SHAFT</b> Footnote (1)						SAE 8-BOLT OPENING				
								PTO DRIVE GEAR DATA: 39T 6P 20° Spur LOCATION: Front    PLMF: .810 PLV: 1702 FPM    RPM: 1,000				
6-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM of PTO	
				HI	LO	REV					TORQUE	HP
SINGLE GEAR												
SINGLE SPEED MULTI GEAR	TG8S-U6804-C3BX	2, 4	Crnk	59					Included	Cable	285	54
	TG8S-U6805-C3BX	2, 4	Crnk	76					Included	Cable	270	51
	TG8S-U6806-C3BX	2, 4	Crnk	99					Included	Cable	245	47
	TG8S-U6807-C3BX	2, 4	Crnk	117					Included	Cable	230	44
	TG8S-U6808-C3BX	2, 4	Crnk	144					Included	Cable	230	44
	TG8S-U6809-C3BX	2, 4	Crnk	150					Included	Cable	205	39
	TG8S-U6812-C3BH	2, 4	Crnk	184					Included	Cable	210	40
	TG8S-U6813-C3BH	2, 4	Crnk	210					Included	Cable	210	40
	TG8S-U6815-C3BH	2, 4	Crnk	236					Included	Cable	195	37
TG8S-U6818-C3BH	2, 4	Crnk	280					Included	Cable	175	33	
SH SERIES	SH8S-U6005-E3BX		Crnk	77					Included	Elec/Air	400	76
	SH8S-U6807-E3BX	4	Crnk	113					Included	Elec/Air	400	76
	SH8S-U6809-E3BX	4	Crnk	140					Included	Elec/Air	375	71
CLUTCH SHIFT	CS8S-U6003-E3BX		Crnk	54					Included	Power	300	57
	CS8S-U6004-E3BX		Crnk	70					Included	Power	300	57
	CS8S-U6005-E3BX		Crnk	77					Included	Power	300	57
	CS8S-U6806-E3BX		Crnk	90					Included	Power	300	57
	CS8S-U6807-E3BX	4	Crnk	113					Included	Power	300	57
	CS8S-U6809-E3BX	4	Crnk	140					Included	Power	275	52
1 FWD. 1 REV.	RL8S-U6803-L3BX	3	Crnk	43		43			Included	Lever	200	38
	RL8S-U6805-L3BX		Crnk	89		89			Included	Lever	200	38
ADAPTER TO CHANGE ROTATION		40TU6886-1 Change PTO arrangement to "2", multiply speed by 1.4						REFER TO ADAPTER GEAR ASSEMBLIES IN INDEX				

8-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM of PTO	
				HI	LO	REV					TORQUE	HP
SINGLE SPEED MULTI GEAR	828S-U6805-L3CX		Crnk	54					Included	Lever	500	95
	828S-U6808-L3CX		Crnk	86					Included	Lever	450	85
	828S-U6809-L3CX		Crnk	106					Included	Lever	410	78
	828S-U6810-L3CX		Crnk	115					Included	Lever	410	78
	828S-U6812-L3CX		Crnk	132					Included	Lever	375	71
	828S-U6813-L3CX		Crnk	153					Included	Lever	375	71
	828S-U6815-L3CX		Crnk	167				(2) 23M80062 23M80248	Included	Lever	350	67
	828S-U6819-L3CX		Crnk	205				20MK8817	Included	Lever	300	57
1 FWD. 1 REV.												



**IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION**

**FOOTNOTES:**

- 1 Speeds shown with main transmission in direct drive.
- 2 TG Series Input Gear: #03T34284 — Refer to kit program on pages 10 & 11.
- 3 RL Series with combined reduction gear box.
- 4 Optional: U68 Input Gear can be replaced by S68 Input Gear to obtain output speed 92% of speed shown. Add spacer 23M80190 and stud kit 20MK8808.