


CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

FULLER TRANSMISSION								RIGHT SIDE ONLY (BOTTOM OPENING TURN PAGE)				
	TO-905A, TO-905D, TO-955AL, TO-955ALL, TO-955DLL, RTO-1157DL, RTO-1157DLL, TO-11605D Footnote (8)							SAE 6-BOLT OPENING				
								PTO DRIVE GEAR DATA:				
								45T 6P 20° PA Spur	PLMF: 1.085			
								LOCATION: Front	RPM: 820			
								PLV: 1610 FPM				
6-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE%			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM OF PTO	
				HI	LO	REV					TORQUE	HP
SINGLE GEAR												
SINGLE SPEED MULTI GEAR	TG6S-U6804-C1BX	1, 2, 4, 6	Opp	55					Included	Cable	285	54
	TG6S-U6805-C1BX	1, 2, 4, 6	Opp	72					Included	Cable	270	51
	TG6S-U6806-C1BX	1, 2, 4, 6	Opp	94					Included	Cable	245	47
	TG6S-U6807-C1BX	1, 2, 4, 6	Opp	111					Included	Cable	230	44
	TG6S-U6808-C1BX	1, 2, 4, 6	Opp	136					Included	Cable	230	44
	TG6S-U6809-C1BX	1, 2, 4, 6	Opp	142					Included	Cable	205	39
	TG6S-U6812-C1BH	1, 2, 4, 6	Opp	174					Included	Cable	210	40
	TG6S-U6813-C1BH	1, 2, 4, 6	Opp	199					Included	Cable	207	39
	TG6S-U6815-C1BH	1, 2, 4, 6	Opp	224					Included	Cable	184	35
	TG6S-U6818-C1BH	1, 2, 4, 6	Opp	264					Included	Cable	155	29
SH SERIES	SH6S-U6005-E1BX	1, 4	Opp	72					Included	Elec/Air	400	76
	SH6S-U6807-E1BX	1, 4, 6	Opp	107					Included	Elec/Air	383	73
	SH6S-U6809-E1BX	1, 4, 6	Opp	133					Included	Elec/Air	308	59
	SH6S-U6812-E1BX	1, 4, 6	Opp	176					Included	Elec/Air	231	44
CLUTCH SHIFT	CS6S-U6003-E1BX	1, 4	Opp	51					Included	Power	300	57
	CS6S-U6004-E1BX	1, 4	Opp	66					Included	Power	300	57
	CS6S-U6005-E1BX	1, 4	Opp	72					Included	Power	300	57
	CS6S-U6806-E1BX	1, 4	Opp	85					Included	Power	300	57
	CS6S-U6807-E1BX	1, 4, 6	Opp	107					Included	Power	300	57
	CS6S-U6809-E1BX	1, 4, 6	Opp	133					Included	Power	275	52
	CS6S-U6812-E1BX	1, 4, 6	Opp	176					Included	Power	231	44
1 FWD. 1 REV.	RL6D-U6803-L3BX	3, 4, 7	Opp	41		41		23M60200S	20MK6602	Lever	200	38
	RL6D-U6805-L3BX	4, 7	Opp	84		84		23M60200S	20MK6602	Lever	200	38
ADAPTER TO CHANGE ROTATION		4, 5	40TU6855-1				REFER TO ADAPTER GEAR ASSEMBLIES IN INDEX					



8-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE%			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM OF PTO	
				HI	LO	REV					TORQUE	HP
SINGLE SPEED MULTI GEAR												
1 FWD. 1 REV.												




IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION

- FOOTNOTES:**
- 1 Direct mount pumps will not clear bulge on right side unless adapter is used.
 - 2 TG Series Input Gear: #03T34284 — Refer to kit program on pages 10 & 11.
 - 3 RL Series with combined reduction gear box.
 - 4 For vehicles with spring hanger interference use the 40TU6855-1 adapter. Not applicable for direct mount pumps. Refer to adapter gear assemblies in the table of contents for additional space requirements.
 - 5 Typical adapter used to clear frame interference. 40TU6845-1 & 40TU6830-1 are also available options. Chassis with clutch slave cylinder located at bottom of transmission, the 40TU6830-1 is recommended.
 - 6 Optional: U68 input gear can be replaced by S68 input gear to obtain output speed 92% of speed shown. Add spacer 23M60200S and stud kit 20MK6603.
 - 7 Do not use for continuous duty applications.
 - 8 PTO torque rating shown is maximum calculated PTO rating which will not exceed the 500 lb.ft. rating set by Eaton for their transmissions with roller bearings. Refer to Eaton bulletin TMIB-0127. Maximum PTO torque must not exceed this rating or the PTO rating shown on page 22 of the General Information section.

CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

FULLER TRANSMISSION								BOTTOM OPENING ONLY (RIGHT SIDE TURN PAGE)				
 <p style="text-align: center;">TO-905A, TO-905D, TO-955AL, TO-955ALL, TO-955DLL, RTO-1157DL, RTO-1157DLL, TO-11605D Footnote (6)</p>								SAE 8-BOLT OPENING				
								PTO DRIVE GEAR DATA:				
								47T 6P 20° PA Spur	PLMF: .810			
								LOCATION: Front	RPM: 820			
								PLV: 1682 FPM				
6-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE%			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM OF PTO	
				HI	LO	REV					TORQUE	HP
SINGLE GEAR												
SINGLE SPEED MULTI GEAR	TG8S-U6804-C1BX	1, 4	Opp	58					Included	Cable	285	54
	TG8S-U6805-C1BX	1, 4	Opp	76					Included	Cable	270	51
	TG8S-U6806-C1BX	1, 4	Opp	98					Included	Cable	245	47
	TG8S-U6807-C1BX	1, 4	Opp	116					Included	Cable	230	44
	TG8S-U6808-C1BX	1, 4	Opp	142					Included	Cable	230	44
	TG8S-U6809-C1BX	1, 4	Opp	148					Included	Cable	205	39
	TG8S-U6812-C1BH	1, 4	Opp	182					Included	Cable	210	40
	TG8S-U6813-C1BH	1, 4	Opp	207					Included	Cable	199	38
	TG8S-U6815-C1BH	1, 4	Opp	233					Included	Cable	176	34
	TG8S-U6818-C1BH	1, 4	Opp	276					Included	Cable	148	28
SH SERIES	SH8S-U6005-E1BX		Opp	76					Included	Elec/Air	400	76
	SH8S-U6807-E1BX	4	Opp	111					Included	Elec/Air	366	70
	SH8S-U6809-E1BX	4	Opp	139					Included	Elec/Air	295	56
	SH8S-U6812-E1BX	4	Opp	184					Included	Elec/Air	221	42
	SH8S-U6813-E1BX	4	Opp	214					Included	Elec/Air	191	36
CLUTCH SHIFT	CS8S-U6003-E1BX		Opp	53					Included	Power	300	57
	CS8S-U6004-E1BX		Opp	69					Included	Power	300	57
	CS8S-U6005-E1BX		Opp	76					Included	Power	300	57
	CS8S-U6806-E1BX		Opp	89					Included	Power	300	57
	CS8S-U6807-E1BX	4	Opp	111					Included	Power	300	57
	CS8S-U6809-E1BX	4	Opp	139					Included	Power	275	52
	CS8S-U6812-E1BX	4	Opp	184					Included	Power	221	42
	CS8S-U6814-E1BX		Opp	230					Included	Power	178	34
	1 FWD. 1 REV.	RL8S-U6803-L3BX RL8S-U6805-L3BX	2, 5 5	Opp Opp	42 87		42 87		23M80032 23M80032	Included Included	Lever Lever	200 200
ADAPTER TO CHANGE ROTATION			40TU6886-1 + 23M80500 + 23M80062 + 20MK8817					REFER TO ADAPTER GEAR ASSEMBLIES IN INDEX				

8-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE%			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM OF PTO	
				HI	LO	REV					TORQUE	HP
SINGLE SPEED MULTI GEAR	828S-U6805-L1CX		Opp	54					Included	Lever	500	95
	828S-U6808-L1CX		Opp	85					Included	Lever	450	85
	828S-U6809-L1CX		Opp	105					Included	Lever	388	74
	828S-U6810-L1CX		Opp	113					Included	Lever	362	69
	828S-U6812-L1CX		Opp	130					Included	Lever	313	60
	828S-U6813-L1CX		Opp	151					Included	Lever	271	52
	828S-U6815-L1CX		Opp	165				(2) 23M80062	Included	Lever	248	47
	828S-U6819-L1CX		Opp	203				23M80248	20MK8817	Lever	202	38
	1 FWD. 1 REV.											



IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION

FOOTNOTES:

- 1 TG Series Input Gear: #03T34284 — Refer to kit program on pages 10 & 11.
- 2 RL Series with combined reduction gear box.
- 3 When using the 40TU6886-1 adapter to change rotation-change TG Series, CS Series, SH Series, and RL Series to 6-bolt PTO housing (TG6S, CS6S, SH6S, and RL6D respectively). RL Series add 23M60200S + 20MK6603 on PTO side of adapter.
- 4 Optional: U68 input gear can be replaced by S68 input gear to obtain output speed 92% of speed shown. Add spacer 23M80190 and stud kit 20MK8808.
- 5 Do not use for continuous duty applications.
- 6 PTO torque rating shown is maximum calculated PTO rating which will not exceed the 500 lb.ft. rating set by Eaton for their transmissions with roller bearings. Refer to Eaton bulletin TMIB-0127. Maximum PTO torque must not exceed this rating or the PTO rating shown on page 22 of the General Information section.