

NEW PROCESS TRANSMISSION
540, 540C, 540CD, 540DD, 540FD, 540GD, 540R, 540T, 540W

MUNCIE POWER PRODUCTS, INC. QR REFERENCE

RIGHT SIDE ONLY

SAE 6-BOLT OPENING

PTO DRIVE GEAR DATA:

20T 7.19P 16D53'01"PA 33D30'R.H.

LOCATION: FRONT

PLMF: 1.047

PLV: 398 FPM

RPM: 457

PTO MODEL	NOTES	ROT	HI	LO	REV	ADAPTER	SPACER	STUD KIT	SHIFT	TRQ	HP
SG6D-N7110-L1AX		CRNK	40				23M60032S	INCLUDED	LEVER	130	25
SG6S-N7110-C1AX		CRNK	40					INCLUDED	CABLE	130	25
RG6D-N7113-L1BX		CRNK	55		44		23M60240S	20MK6603	LEVER	140	26

FOOTNOTE:

No Adapter Available

NEW PROCESS TRANSMISSION
540, 540C, 540CD, 540DD, 540FD, 540GD, 540R, 540T, 540W

MUNCIE POWER PRODUCTS, INC. QR REFERENCE

LEFT SIDE ONLY

SAE 6-BOLT OPENING

PTO DRIVE GEAR DATA:

15T 6P 20D PA SPUR

LOCATION: REAR

PLMF: 1.035

PLV: 244 FPM

RPM: 373

PTO MODEL	NOTES	ROT	HI	LO	REV	ADAPTER	SPACER	STUD KIT	SHIFT	TRQ	HP
SG6D-U6810-L2AX	2	CRNK	25			40TA0810	23M60032S + 23M60093S	20MK6602	LEVER	130	25
SG6S-U6810-C2AX	2	CRNK	25			40TA0810	23M60093S	20MK6602	CABLE	130	25
TG6S-U6813-C4BH	1,2	OPP	31			40TA0810	23M60093S	20MK6602	CABLE	210	40
TG6S-U6815-C4BH	1,2	OPP	35			40TA0810	23M60093S	20MK6602	CABLE	195	37
TG6S-U6818-C4BH	1,2	OPP	40			40TA0810	23M60093S	20MK6602	CABLE	175	33
RG6D-U6813-L4BX	2,3	CRNK	33		27	40TA0810	23M60093S + 23M60200S	20MK6602	LEVER	140	26

FOOTNOTE:

No Adapter Available

1. TG Series Input Gear: #03T34284 -- Refer to kit program on page 10 & 11.
2. Due to adjacent gear interference adapter gear is required. Ten (10) inches of clearance between transmission and frame are needed for mounting.
3. Also requires 20MK6604 Stud Kit.