


CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

VOLVO TRANSMISSION								REAR ONLY				
		ATO2512C, ATO3112C, ATO2612C, ATO2612D, ATO3112D, TMD12AO TMD13AO, TMD14AO, TMD13AFO-HD, TMD14AFO-HD Footnotes (1, 2, 3, & 5)						METRIC 4-BOLT OPENING				
								PTO DRIVE GEAR DATA:				
LOCATION: PLV:			PLMF: RPM:									
6-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE%			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM OF PTO	
				HI	LO	REV					TORQUE	HP
SINGLE GEAR	RS4S-P81V8-P1CX	1, 2, 3, 6	Opp	88					199K8030000	Air	442	84
SINGLE SPEED MULTI GEAR	RS4S-P86VM-P1CX	1, 2, 3, 4	Crnk	117					199K8020000	Air	331	63
	RS4S-P86VN-P1CX	1, 2, 3, 4	Crnk	81					199K8020000	Air	369	70
	RS4S-P93VN-P1CX	1, 2, 3, 4, 7	Crnk	81					199K8020000	Air	368	70
SH SERIES												
CLUTCH SHIFT												
1 FWD. 1 REV.												
ADAPTER TO CHANGE ROTATION			No Adapter Available							REFER TO ADAPTER GEAR ASSEMBLIES IN INDEX		

8-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE%			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM OF PTO	
				HI	LO	REV					TORQUE	HP
SINGLE SPEED MULTI GEAR												
1 FWD. 1 REV.												

PTO SERIES & HOUSING DESIGNATOR
 GEAR PITCH
 INTERNAL RATIO
 SHIFT OPTIONS (see page 20)
 ASSEMBLY ARRANGEMENT (see page 20)
 OUTPUT SHAFT (see page 20)
 SPECIAL OPTIONS (see page 20)


EX: TG 6S - U68 07 - C 1 B X

IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION


FOOTNOTES:

- Speed shown in Lo range. Multiply speed by 1.27 for Hi range.
- Rear mounted PTO model shown with 1310 Series companion flange. Connection to Volvo system required.
- For Volvo I-Shift or Mack M-Shift transmission, the chassis needs to be ordered with PTO prep package. PTO shift option "P" to use chassis supplied PTO activation. The vehicle ECU must be programmed by Dealer for PTO operation.
- For continuous duty applications add lube kit 195KLB37000.
- Direct mount pump limited to 25 lb. Max weight without support to transmission. See page 18 in General Information.
- P81 Series is a through shaft PTO and does not offset the output shaft. Direct mount pumps will interfere on P81. Use for driveline applications only.
- P93 Series PTO has two independently operated outputs in addition to the main input activation to Volvo transmission. Each output has the same speed and rotation as shown. Order activation kit for each separate output, 48TK3928. Add indicator switch 194KSP19000 for each output.

CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

VOLVO TRANSMISSION												
		ATO2512C, ATO3112C, ATO2612C, ATO2612D, ATO3112D, TMD12AO TMD13AO, TMD14AO, TMD13AFO-HD, TMD14AFO-HD						PTO DRIVE GEAR DATA:				
6-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM OF PTO	
				HI	LO	REV					TORQUE	HP
SINGLE GEAR												
SINGLE SPEED MULTI GEAR	NO PTO OPENING - SEE OTHER SIDE											
SH SERIES												
CLUTCH SHIFT												
1 FWD. 1 REV.												
ADAPTER TO CHANGE ROTATION		No Adapter Available							REFER TO ADAPTER GEAR ASSEMBLIES IN INDEX			

8-BOLT TYPE	PTO MODEL NUMBER	FOOT NOTES	SHAFT ROTATION	ENGINE %			ADAPTER	SPACER	STUD KIT	SHIFT TYPE	INTERMITTENT RATING @ 1,000 RPM OF PTO	
				HI	LO	REV					TORQUE	HP
SINGLE SPEED MULTI GEAR												
1 FWD. 1 REV.												



EX: TG 6S - U68 07 - C 1 B X

IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION

FOOTNOTES: